

Developmental Studies of High Current Linac for Indian ADS program

P. Singh

**Bhabha Atomic Research Centre
Mumbai, India**

Plan of the talk:

- 1. What is an Accelerator Driven sub-critical reactor System (ADS)**
- 2. Why is ADS so important to us?**
- 3. Accelerator Configuration**
- 4. Developmental studies of high intensity proton linac (20 MeV LEHIPA)**
- 5. Status of the project**
- 6. Summary & conclusions.**

➤ At the present consumption level, known reserves for coal, oil and gas correspond to duration of:

➤ Coal: 230 yrs

➤ Oil: 45 yrs

➤ Gas: 65 yrs

➤ Nuclear Power appears to be an inevitable option as future energy source; but disposal of nuclear waste is an important issue of concern in harnessing nuclear energy through “critical reactors”, which needs to be addressed satisfactorily.

Annual yield of Plutonium & Minor Actinides and (some) fission products in spent fuel from 1 GWe LWR plant operation.

Isotope	Mass (kg/yr)	T_{1/2} (year)	Fission Products
²³⁸ Pu	4	87.7	
²³⁹ Pu	166	24110	⁸⁹ Sr – ⁹⁰ Y.... Short-lived
²⁴⁰ Pu	76.7	6550	¹³⁷ Cs .. T _{1/2} ~ 30 years
²⁴¹ Pu	25.4	14.4	⁹⁹ Tc Truly Long-lived, ¹³⁵ Cs T _{1/2} ~ 10 ⁴ -10 ⁶ ¹²⁹ I years Others are ⁹³ Zr, ¹⁰⁷ Pd
²⁴² Pu	15.5	3.5x 10 ⁵	
²³⁷ Np	14.5	2.14x10 ⁶	
²⁴¹ Am	16.6	432.6	
²⁴³ Am	3	737	
²⁴⁴ Cm	0.6	18.1	




FIG. A-3. The ranges of levelized costs associated with new construction as estimated in seven recent studies for electricity generating technologies in different countries (PV: photovoltaic).



World Thorium Resources

Country	Reserves (tons)
Australia	300,000
India	290,000
Norway	170,000
USA	160,000
Canada	100,000
S. Africa	35,000
Brazil	16,000
Other Countries	95,000
World total	1,200,000

India needs a system which can...


- Produce Energy
- Transmute the high level long-lived radioactive waste
- Can use efficiently Thorium resources

SCHEMATIC OF ACCELERATOR-DRIVEN SYSTEM




Spallation reaction of high-energ proton with lead nucleus

Thorium breeding into fissile uranium.




Uranium (bulk) ${}^{238}\text{U}$ breeding into fissile plutonium.



Accelerator-Driven Sub-critical reactor can be used for:


- **Generating nuclear power with Thorium as fuel,**
- **Transmutation of nuclear waste discharged from nuclear reactor of U-Pu fuel cycle.**

ACCELERATOR DRIVEN ENERGY AMPLIFIER



Most cost effective way to produce neutrons

- By Spallation process with GeV energy protons striking on high Z target.
- Number of neutrons per proton per Watt of beam power reaches a plateau just above 1 GeV.



$$P_{thermal} (MW) = E_{fission} (MeV) I (A) \frac{\nu_s}{\nu} \frac{k}{1-k}$$

Proton Energy : 1 GeV

$\nu_s = 25$ neutrons/proton

$\nu = 2.5$ neutrons/fission

$P_{electrical} = 500$ MW (1500 MW (th))

$K=0.95$

$P_{thermal}$ (MW)	I (mA)
1000	29.2
1500	43.9
2000	58.5
2500	73.1
3000	87.7

Some of the ADS Projects around the world

- JAPAN Under its OMEGA (Option Making Extra Gains of Actinides and FP), that is extension of its earlier Actinides Burner Reactor (ABR).
- KOREA Under its HYPER (Hybrid Power Extraction Reactor) programme.
- ITALY Under its TRASCO (TRANsmutazion SCOrie) Programme and, Industrial project undertaken by ANSALDO for EC.
- CHINA Proposed as CIAE+IHEP project but under an un-named ADS programme of Sino-Italian collaboration.
- BELGIUM Under MYRRHA project as extension of ADONIS (Accelerator-Driven Operated New Irradiation System) programme for radioisotope production.
- FRANCE Its CNRS/IN2P3 institutes are spearheading waste incineration R&D with spinoff of its TRISPAL activities for accelerator to ADS.
- GERMANY Activities under FZK in the yet un-named programme.
- RUSSIA Undertaken several study projects in ITEP/ISTC against the EC/US funding.
- USA Earlier as ATW. Now AAA (Advanced Accelerator Applications) aiming for having ADTF in 10 years from 2001. Full technological Demo in next 10 years.

The technologically most important and challenging part in ADS scheme is the High Power Proton Accelerator.

The main requirements from this accelerator are:-

- ➔ High Reliability
- ➔ High Beam Power
- ➔ CW Operating Mode
- ➔ High Conversion Efficiency
- ➔ Minimum Beam Loss
- ➔ Easy Maintenance & Serviceability

The linac option seems attractive because higher beam current can be achieved.

The Linac is divided into three parts for convenience.

- Low Energy (upto 20 MeV)
- Medium Energy (20 MeV to 100 MeV)
- High Energy (> 100 MeV)

The accelerating structures used at different energies are:-


- Low Energy – RFQ, DTL/CCDTL /SDTL
- Medium Energy - CCDTL /SDTL
- High Energy – CCL, Superconducting structures

Main Design issue is beam loss control.

Space charge forces are strongest in the low energy end.

So particular care must be taken to design this part.


Scheme for Indian ADS Programme



Main design issue:

- beam loss < 1 Watt/m.
- Avoid halo formation

Layout of 20 MeV Linac Section



ECR Ion source RFQ 4 Vane type 20 MeV, 30 mA
50 keV, 35mA. 3MeV, 30 mA Alvarez type DTL

LEBT : Low Energy Beam Transport System

RFQ : Radio Frequency Quadrupole


MEBT : Medium Energy Beam Transport System

DTL : Drift Tube Linac



ECR Ion Source

P. Roychowdhary et al, APPD, BARC

- Five electrodes
- 2.45 GHz
- 50 keV
- 50 mA
- 0.02π cm-mrad




Schematic of the ECR Ion Source



Testing in progress

20 MeV Linac: Transport Line LEBT




2.45 GHz
ECR Ion source
50 keV, 35mA.

352.21 MHz,
4-Vane type RFQ
3-MeV, 30 mA



352.21 MHz,
20 MeV, 30 mA
Alvarez type DTL

Low Energy Beam Transport (LEBT) System



Error Analysis of Solenoids

Beam Energy = 50 keV
 Beam current = 30 mA
 RMS Normalized Beam Emittance = 0.02π cm mrad



Tolerance on solenoid strength = ± 30 Gauss


Space Charge Compensation in LEBT

➡ Beam transport in the LEBT is mostly determined by space charge forces

➡ Space charge compensation can restrict increase in beam size and emittance growth significantly.



How it is done?

- Introduce a residual gas in the background.
- The beam ionizes the residual gas.
- Electrons are trapped by the space charge potential of the beam.
- So space charge is gradually reduced.





Effect of Non-Linear space charge on beam dynamics in LEBT


- KV distribution being uniform causes linear space charge forces.
- Any kind of non-uniformity in the density will give rise to non-linear space charge.
- Non-linearity of the space charge field reflects in emittance increase as well as in waist diameter.



With KV- distribution



With Parabolic distribution



KV: Kapchinskij-Vladimirskij distribution

Low Energy Beam Transport Line

- Used to match the dc beam from the ion source to the RFQ.
- Two solenoids (~2 kG) are used.

Beam Energy = 50 keV

Beam current = 30 mA

RMS Norm. Emittance = 0.02π cm mrad

Max. beam size in the LEBT = 13 cm


Total length = 1.85 m.

Effect of Space Charge Compensation on beam dynamics

Degree of Space Charge Compensation (%)	I_{eff} (mA)	Max. Beam size (cm)	Emit at end of LEBT (cm mrad)	Transmission through the RFQ (%)
0	30	13.0	0.02081	97.1
90	3.0	7.0	0.02003	96.0
95	1.5	6.8	0.02000	97.3
98	0.6	6.4	0.02000	97.4

Effect of Emittance on Transmission


If the **emittance** of the input beam to the RFQ is more than the designed value the **transmission drops drastically**.



Critical Input parameter for RFQ design:




rms emittance of the beam from the ion source



Fabricated & tested at RRCAT, Indore

20 MeV Linac: Accelerating Structure RFQ



2.45 GHz
ECR Ion source
50 keV, 35mA.

352.21 MHz,
4-Vane type RFQ
3-MeV, 30 mA

352.21 MHz,
20 MeV, 30 mA
Alvarez type DTL

Principle of RFQ

Particles experience alternate gradient electric focusing which is stronger than magnetic focusing for low velocity particles.









Figure 2: A RELAX3D model of the exit region showing three regular cells, a transition cell and a short unmodulated end section.



The longitudinal fields for acceleration are produced by modulating the electrodes longitudinally.


The RFQ simultaneously **Focuses, Bunches** and **Accelerates** the beam.

Full 3D model of the RFQ



RFQ Cavity design (3D)

End Regions of the RFQ



Magnetic Field lines in Quadrupole mode at end

Boundary conditions

$$E_p = 0 \quad B_n = 0$$

The RFQ resonator has to be closed at both ends. The longitudinal magnetic field lines cannot be perpendicular to the end plate. It must be parallel.

Vanes do not extend to the end plate and in addition are cut to facilitate turning of the magnetic field.


Operating Mode: TE_{210} like mode

Dominant modes
 TE_{21} - Quadrupole
 TE_{11} - Dipole

Coupling Cell

- For smaller length the number of modes in a given frequency range is less.
- Field tilt effects can become important for structures with a length of few wavelengths.

The RFQ is 4 m long. For better stability it will be made in smaller sections which will be **resonantly coupled**.





The coupling plates separate the segments and prevent the magnetic field lines from continuing from one segment to the next. The gap between the vanes provides capacitive coupling.


RFQ Parameters

1. Bunching 2. Focusing 3. Acceleration

Frequency	352.21 MHz
Energy	50 keV/ 3 MeV
Input current	30 mA
Vane voltage	80 kV
Avg. Aperture R_0	3.63-4.53 mm
Length	4 m
Total RF power	500 kW
Transmission	98 %



3 MeV Radio Frequency Quadrupole





Coupling cell

Tuners

- 64 tuners --- 16 per quadrant, symmetrically placed in each quadrant
- Static tuners.
- Cooling required.
- Tuning Range : 468.5 kHz/mm (all)



Vacuum ports

- 24 vacuum ports
- Frequency detuning : 745.86 kHz (all)




Variation of dipolar and quadrupolar frequencies with RFQ length

RFQ Length = 4 m




$$\omega_n^2 = \omega_0^2 + (n\pi c/L)^2$$

Boundary conditions
 $E_p = 0$ $B_n = 0$




Thermal Analysis of the RFQ





Heat flux on Cavity walls of the RFQ



5845-84734 (W/m²)



Temperature distribution at inlet and outlet




Deflections at inlet and outlet



- ❖ Coolant temperatures are 16°C in vane channels and 20°C in wall channels
- ❖ Frequency sensitivity with vane water temperature is -46 kHz/°C
- ❖ Frequency sensitivity with wall water temperature is +35 kHz/°C

20 MeV Linac: Beam Stop





2.45 GHz
ECR Ion source
50 keV, 35mA.

352.21 MHz,
4-Vane type RFQ
3-MeV, 30 mA

352.21 MHz,
20 MeV, 30 mA
Alvarez type DTL


High flux neutron Facility



Neutron Yield for Beryllium target

$$S_0(E_p) = 4.476 \times 10^{11} \times E_p^{1.886} \times I \text{ n/s}$$

Beam Stop



Beam stop will be used to stop the beam of protons in order to test the quality of the beam during commissioning.

Beam will be under full power and continuous

- 20 MeV, 30 mA Beam
- Total power 600 kW


Conical target for beam dump.

400 keV RFQ parameters


Parameters	Value
Frequency	350 MHz
Injection energy	50 keV
Final energy	400 keV
RFQ length	1.05 m
RF Power dissipated	68 kW
Beam current	1 mA
Norm. RMS emittance	0.015 π cm-mrad
Vane voltage	44 kV
Transmission efficiency	96 %
Peak surface field	32.9 MV/m
Average radius	1.873 cm
Maximum Modulation	1.287


If the **emittance** of the input beam to the RFQ is more than the designed value the **transmission drops drastically**.

Transmission at the end of RFQ : 94.8%



Variation of RFQ parameters along the length.







RF Coupler design

◆ Coupler Dimensions:

- Coax ID: 15 mm
- Coax OD: 34.5mm
- Loop Diameter: 10 mm
- Loop Depth: 12 mm (max)




LAYOUT OF 50 kW RF COUPLER ASSEMBLY




50 kW Coaxial Coupler specifications:

- Return Loss: Better than -25 db
- Coupling Coefficient: Variable from 1.2 to 0.7
- Max delta T on window: < 30°C
- Max. temperature on loop: 120°C
- Frequency Shift: < 2 MHz



250 kW, 352 MHz Iris Coupler Development



RF Simulation Model of Iris Coupler

- Ten No. Waveguide couplers required for 20 MeV LEHIPA
- WR2300 to Iris transition using double ridge waveguide
- Tapered transition with variable and constant ridge width has been studied.
- Thermo -Structural analysis and design in progress

Length of iris (cm)	External Q
8.15	30710.0
10.15	5844.0
10.72	4052.5
10.77	3895.1
12.15	1861.0
14.15	802.3
16.15	412.7









Fig 6. β vs length of the iris.


External Q and Coupling Coefficient variation with Iris length







20 MeV Linac: Transport Line **MEBT**




2.45 GHz
ECR Ion source
50 keV, 35mA.

352.21 MHz,
4-Vane type RFQ
3-MeV, 30 mA


352.210 MHz,
20 MeV, 30 mA
Alvarez type DTL

Medium Energy Beam Transport Line

- Beam from the ion source is not round and is pulsed.
- So now four transverse parameters of the beam have to be matched to the input of the DTL.
- The transverse matching is achieved by using 4 quadrupoles.
- RF buncher is used for longitudinal matching.



20 MeV Linac: Accelerating Structure DTL






2.45 GHz
ECR Ion source
50 keV, 35mA.

350 MHz,
4-Vane type RFQ
3-MeV, 30 mA

350 MHz,
20 MeV, 30 mA
Alvarez type DTL

The Drift Tube Linac

- ❖ The DTL tank is a resonant cavity excited in the TM_{010} mode.
- ❖ It consists of drift tubes connected to tank by stems separated by gaps.
- ❖ Quadrupoles are mounted in drift tubes for focusing.




DTL

Cavity Parameters



Frequency (MHz)	352.21
Cavity Diameter (cm)	52
Drift tube diameter (cm)	12
Bore radius (cm)	1.1
Face Angle (deg)	0
Corner radius (cm)	1.5
Inner corner rad. (cm)	0.5
Outer corner rad. (cm)	0.5



Tuners





Post Couplers placed every third DT in the first tank



Vacuum port

- 5 rectangular slots per vacuum port
- Slots orientation along the direction of surface current
- Port Conductance: 1400 l/s
- No. of vacuum ports in first tank: 2
- Frequency detuning due to the vacuum ports is negligible (13.39 kHz with both ports)


Comparison of DTL and CCDTL



40-100 MeV

CCDTL at CERN

Parameter	DTL	CCDTL
Energy Range (MeV)	3-40	40-100.2
Frequency (MHz)	352.21	704.42
Current (mA)	29.3	29.3
Quadrupole Gradient (T/m)	43	62.4-19.5
Eff. Length of Quad. (cm)	4.72	8.0
No. of Quadrupoles	155	186
Avg. Acc. Gradient (MV/m)	2.5	1.37
Aperture Radius (cm)	1.0	1.2
Total Length (m)	24	70




The Family of H-Mode Resonators

IH-RFQ


Low and Medium - β Structures in H-Mode Operation

4-vane RFQ



IH-Structure


CH-Structure



H-type DTL's




r.t. IH-DTL
 $W < 30$ MeV
30-250 MHz
copper plated steel



r.t. CH-DTL
 $W < 150$ MeV
150-700 MHz




s.c. CH-DTL
 $W < 150$ MeV
150-700 MHz
bulk niobium




RT SR section

Solution is Room Temperature Spoke Resonator (aka Cross-bar H-type resonators) section from 3 MeV to 15 MeV .




Solenoid in individual cryostat

Shape Optimization



RT TSR section




The main advantage of RT SR is its high shunt



H-type DTL's


KONUS (Combined 0° Structure) beam dynamics
Example: GSI HLI IH cavity

Quadrupole Triplet Channel :





SC Spoke Resonator

Shepard, Kelly, Fuerst, presented
at **PAC 2003, SRF 2003**




The cavity can operate cw at gradients up to 12 MV/m, producing more than 4.5 MV of accelerating potential




Superconducting cavity (IPN Orsay) – 5 cells, 700 MHz, $\beta=0,65$


In order to efficiently design a linac it is necessary to divide it in sections, each using a different cavity geometry in an energy range.




$\beta_G = 0.47$



$\beta_G = 0.62$





$\beta_G = 0.80$




Design of Superconducting Cavity

Parameters	$\beta_G = 0.47$	$\beta_G = 0.62$	$\beta_G = 0.8$
No. of Cells	5	5	5
Diameter D (cm)	36.27	35.83	37.34
Dome B (cm)	2	3	5.5
Dome A/B	1.5	1.5	1
Wall Angle α_w (deg)	5	5	7
Iris a/b	1.2	1	0.5
Bore Radius (cm)	4	4	4



3-D view of the cavity at 700 MHz



SUPERFISH output plot showing electric field lines for single cell cavity without beam tube

100 MeV – 1 GeV SC Linac

(Initial design with 5 MV/m gradient)

Parameter	$\beta_G = 0.47$	$\beta_G = 0.62$	$\beta_G = 0.80$
Energy Range (MeV)	98.6-198.3	198.3-498.3	498.3-1008.3
Frequency (MHz)	704.42	704.42	704.42
Current (mA)	29.3	29.3	29.3
Trans. Focusing lattice	Doublet	Doublet	Doublet
Lattice Period (cm)	300.1	608.0	810.7
Quadrupole gradient (T/m)	5.8-5.37	4.5	4.4
Eff. Length of Quad (cm)	35	40	45
Synch. Phase (degrees)	-30	-23.44	-23.44
Cavities/cryomodule	2	3	4
No. of Cryomodules	35	40	51
Aperture Radius (cm)	4.0	4.0	4.0
Total length (762 m)	105.04	243.2	413.46
Norm. Trans. Emitt. (π cm-mrad) ε_x	0.024-0.025	0.025-0.029	0.029-0.030
ε_y	0.024-0.025	0.025-0.028	0.028-0.027
Norm. Long. Emitt. (MeV-deg)	0.327-0.444	0.444-0.482	0.482-0.499

Main parameters of the HINS (8GeV H⁻ linac)

Parameter	RFQ	RT Triple Spoke	Single-spoke	Double-spoke	Triple spoke	TESLA1	TESLA2
Frequency, MHz	325	325	325	325	325	1300	1300
Beta geometrical		0.08 \oplus 0.18	0.21	0.4	0.61	0.81	1.0
Number of accelerating gaps		4	2	3	4	8	9
E _{peak} , MV/m		TBD	32	32	32	45	45
E _{acc} , MV/m		2.3 \oplus 3.7	10.67	10.67	10.67	20.5	22.5
Cavity effective length, cm		15 \oplus 32	13	36.9	85.8	74.7	103.8
Number of resonators		21	16	28	42	56	322
Synchronous phase, deg		-40 (first 6), -40 \oplus -30 ramp	-30	-30	-30 \oplus -20 ramp	-30	-16
Input energy, MeV	0.06	3.0	15.6	33	110	400	1120
Output energy, MeV	3.0	15.6	33	110	402	1120	8021
Length of the section, m	3.8	10.4	12.5	17.2	64	77	554
Maximum coupler power, for 26 mA H ⁻ beam, kW		54	(25.5) TBD	(102) TBD	(238) TBD	398	607



Global Accelerator Parameters for 500 GeV cms.

Parameter	Value	Units
Center-of-mass energy	500	GeV
Peak luminosity	2×10^{34}	$\text{cm}^{-2}\text{s}^{-1}$
Availability	75	%
Repetition rate	5	Hz
Duty cycle	0.5	%
Main Linacs		
Average accelerating gradient in cavities	31.5	MV/m
Length of each Main Linac	11	km
Beam pulse length	1	ms
Average beam current in pulse	9.0	mA
Damping Rings		
Beam energy	5	GeV
Circumference	6.7	km
Length of Beam Delivery section (2 beams)	4.5	km
Total site length	31	km
Total site power consumption	230	MW
Total installed power	~ 300	MW

Parameters of SC Linac (15 MV/m)

Parameter	$\beta_G = 0.49$	$\beta_G = 0.62$	$\beta_G = 0.80$
Energy Range (MeV)	100.2-197.2	197.2-421.3	421.3-1016.5
Frequency (MHz)	704.42	704.42	704.42
Current (mA)	29.3	29.3	29.3
Trans. Focusing lattice	Doublet	Doublet	Doublet
Lattice Period (cm)	304.27	607.90	810.47
Quadrupole gradient (T/m)	5.80-4.31	4.50-4.99	4.40
Eff. Length of Quad (cm)	35	40	45
Synch. Phase (degrees)	-30	-35.24	-34.37
Cavities/cryomodule	2	3	4
No. of Cryomodules	12	15	23
Aperture Radius (cm)	4.0	4.0	4.0
Total length (306 m)	34.76	88.15	183.33
Norm. Trans. Emitt. (π cm-mrad) ϵ_x, ϵ_y	0.023-0.030 0.024-0.027	0.030-0.033 0.027-0.030	0.033-0.037 0.030-0.031
Norm. Long. Emitt. (MeV-deg)	0.237-0.241	0.241-0.240	0.240-0.257

Beam Dynamics



- Aperture is more than 16 times the rms beam size in the SC Linac
- Emittance growth is very small
- Transmission through the linac = 100%.

Accelerating Gradient in SC Linac


	5 MV/m				15 MV/m			
IS, LEBT, MEBT:	1	MW	0.5	MeV	1.0	MW	0.5	MeV
RFQ	:0.5	MW	3	MeV	0.5	MW	3	MeV
DTL	: 4	MW	50	MeV	3.0	MW	40	MeV
CCDTL	: 5	MW	100	MeV	6.4	MW	100	MeV
SC Linac	: 27	MW	1	GeV	26.9	MW	1	GeV

Total RF Power: 38 MW

38 MW

Ion source	: 2.0	m	2.0	m
LEBT	: 1.8	m	1.8	m
RFQ	: 4.0	m	4.0	m
MEBT	: 1.5	m	1.5	m
DTL	: 28.0	m	23.0	m (40 MeV)
CCDTL	: 75.0	m	70.0	m
SC Linac	: 762.0	m	306.0	m
Total Length	: 894.3	m	408.3	m

Layout of LEHIPA Building



Summary

- **Physics Design of a 1 GeV, 30 mA Linac has been done**
- **100-1000 MeV part will be superconducting**
- **In Phase I, 20 MeV, 30 mA Linac is being built**
- **Development of prototypes of different sub-systems is in progress**
- **Although work in progress but not covered in detail are RF power, Control systems, Diagnostics, Radiation safety, monitors, Cooling systems, Material development, Cryogenics, Vacuum systems, Shielding, Target and Reactor design**
- **We have made some progress but still miles to go.....**

PARTICIPATING DIVISIONS:

✓ Nuclear Physics Division (NPD)

- ✓ Vacuum Physics and Instrumentation Division (VPID)
- ✓ Accelerator & Pulse Power Division (APPD)
- ✓ Reactor Safety Division (RSD)
- ✓ Centre for Design and Manufacture (CDM)
- ✓ Research Reactor Design & Projects Division (RRDPD)
- ✓ Technical Services Division (TSD)
- ✓ Architecture & Civil Engineering Division (A&CED)
- ✓ Laser and Neutron Physics Section (LNPS)
- ✓ Control Instrumentation Division (CnID)
- ✓ Radiation Safety & Systems Division (RSSD)
- ✓ Electronics Division (ED)
- ✓ Reactor Control Division (RCnD)
- ✓ Reactor Projects Division (RPD)
- ✓ Raja Ramanna Centre for Advanced Technology (RRCAT)

Team Members from NPD

S.V.L.S. Rao

Rajni Pande

Shweta Roy

T. Basak (now at TIFR)

S.C.L. Srivastava

Piyush Jain

Rajesh Kumar

S.K. Singh

P. Singh

P.K. Nema

R.K. Choudhury

S. Kailas

V.C. Sahni

धन्यवाद

Thank You!